

Save Energy by Insulating your Home or Garage!

Knauf Insulation Jet Stream® Ultra Blowing Insulation



Rent a blower for only
\$15.00 a day
with insulation purchase.

GreenFiber Blow in Natural Fiber Insulation



Knauf Insulation Jet Stream® ULTRA Fiber Glass Blowing Insulation is an unbonded, virgin fibrous glass blowing insulation designed with optimal thermal properties and excellent coverage and blowing characteristics. It can be easily installed in open attics of both new and existing structures. Jet Stream ULTRA Fiber Glass Blowing Insulation will not sustain mold growth. The Jet Stream ULTRA insulation is a minimum of 40% post-consumer recycled glass content.

- ULTRA-performance. It never settles.
- ULTRA-fast, ULTRA-easy installation.
- Fills all gaps and voids
- Creates a sound barrier
- Blows fast and smooth
- Noncombustible, non-corrosive
- Will not rot, mildew, or deteriorate
- Packaged in strong poly bag

Today, there is a growing public concern for reducing damage to our environment and dependence on fossil fuels. GreenFiber responds to this concern by offering insulation products endowed with multiple environmental benefits produced in a virtually waste-free manufacturing process. GreenFiber manufactures GreenFiber Insulation for use in attics, floors, and walls of residential new construction and re-insulation applications. GreenFiber provides outstanding thermal performance, fire-resistance and sound control. GreenFiber's Insulation products provide a barrier against air infiltration by filling gaps and voids. GreenFiber consists of 85% recycled content.

- Designed for loose fill attic applications
- Made of 85% recycled paper fibers
- Treated for fire resistance
- Minimal settling
- Manufactured in the USA

82 Garden Spot Road
Ephrata, Pa 17522
717-445-6885



A. B. MARTIN
ROOFING SUPPLY, LLC

Roofing & Siding • Hardware • Lumber

www.abmartin.net

35 Ridge Road
Newville, Pa 17241
717-776-5951

What you should know about R-values

These chart shows the R-value of the insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.



THIS IS GREENFIBER® LOOSE FILL FORMULA INSULATION



Application Coverage Chart		30 lbs (13.6 kg)					INS515LD	
R-Value at 75° F Mean Temp. Valor de resistencia termica (valor R) a 75° F de temperatura media	Minimum Thickness (inches) Espesor minimo (en pulgadas)		Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para el entramado)			Net Coverage (adjusted for 2' x 6' framing on 16' centers) Cobertura neta (con compensación para una estructura de 2' x 6' en centros de 16')		
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	
R 11	3.38	3.04	102.5	9.8	0.293	113.1	8.8	
R 13	4.01	3.61	84.9	11.8	0.353	93.7	10.7	
R 19	5.88	5.29	55.2	18.1	0.544	60.5	16.5	
R 22	6.80	6.12	46.6	21.5	0.644	50.4	19.8	
R 26	8.02	7.22	38.4	26.1	0.782	41.0	24.4	
R 30	9.22	8.30	32.4	30.8	0.925	34.3	29.1	
R 32	9.82	8.84	30.0	33.3	0.999	31.7	31.5	
R 38	11.60	10.44	24.4	40.9	1.23	25.6	39.1	
R 40	12.19	10.97	22.9	43.6	1.31	24.0	41.7	
R 44	13.36	12.03	20.4	49.0	1.47	21.2	47.1	
R 48	14.53	13.07	18.3	54.6	1.64	19.0	52.6	
R 49	14.82	13.34	17.9	56.0	1.68	18.5	54.1	
R 50	15.11	13.60	17.4	57.4	1.72	18.0	55.5	
R 60	17.99	16.19	13.8	72.4	2.17	14.2	70.4	

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTING CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 28.5 LBS.

JET STREAM® ULTRA

Fiber Glass Blowing Insulation



Open Attic Application					
R-Value*	Bags/1,000 SF	Maximum Coverage	Minimum Weight	Initial Installed Thickness	Minimum Settled Thickness**
To obtain an insulation resistance (R-value) of:	The number of bags/1,000 SF of net area should not be less than:	Contents of this bags should not cover more than:	The weight/SF of installed insulation should not be less than:	Installed insulation should not be less than:	Installed insulation should not be less than:
R-60	29.7	33.6 SF	.952 lbs.	19.750*	19.750*
R-49	23.5	42.5 SF	.753 lbs.	16.375*	16.375*
R-44	20.9	47.8 SF	.670 lbs.	14.875*	14.875*
R-38	17.8	56.2 SF	.569 lbs.	13.000*	13.000*
R-30	13.6	73.3 SF	.437 lbs.	10.375*	10.375*
R-26	11.8	85.0 SF	.377 lbs.	9.125*	9.125*
R-22	9.8	102.2 SF	.313 lbs.	7.750*	7.750*
R-19	8.4	119.3 SF	.268 lbs.	6.750*	6.750*
R-13	5.7	175.3 SF	.183 lbs.	4.750*	4.750*
R-11	4.7	210.8 SF	.152 lbs.	4.000*	4.000*

82 Garden Spot Road
Ephrata, Pa 17522

717-445-6885



A. B. MARTIN
ROOFING SUPPLY, LLC

Roofing & Siding • Hardware • Lumber

www.abmartin.net

35 Ridge Road
Newville, Pa 17241

717-776-5951